



TGFU.R20739 Roofing Systems

[Page Bottom](#)

Roofing Systems

[See General Information for Roofing Systems](#)

MILLENNIUM ADHESIVE PRODUCTS INC
17340 MUNN RD
CHAGRIN FALLS, OH 44023 USA

R20739

SINGLE PLY MEMBRANE SYSTEMS

Class A - Ballasted

1. **Deck:** NC

Incline: 2

Insulation (Optional): — Perlite, wood fiber, glass fiber, polyurethane, polyisocyanurate, polystyrene (expanded or extruded), phenolic, perlite/urethane composite, perlite/polyisocyanurate or polystyrene/perlite composite, any combination, any thickness.

Membrane: — Any UL Classified membrane partially adhered with "Weather-Tite Hurricane Force Lap and Membrane Adhesive" applied as nominal 1/2 to 2/3 in. diameter beads with an on-center spacing of 3 to 18-inches.

Surfacing: — River bottom stone (3/4 in. to 1-1/2 in. diameter) at 1000 lb/sq.

Class Class A, B or C (See Note)

1. **Deck:** NC (See Note 1)

Incline: See Note 1

Insulation: — Any UL Classified, any thickness, adhered with "Weather-Tite Pourable Foam Insulation Adhesive."

Membrane: — Any UL Classified modified bitumen system, BUR system or CPE, CSM, CSPE, EPDM, NBP, PIB, PVC, TPO or TRE membrane system suitable for use with any roof insulation.

Note 1: Classification (A, B or C) and maximum incline will be the same as that of the Classified Roofing System (TGFU) currently limited to noncombustible deck.

2. **Deck:** NC (See Note 1)

Incline: See Note 1

Insulation: — Any UL Classified, any thickness, adhered with "Weather-Tite One Step Foamable Adhesive."

Membrane: — Any UL Classified modified bitumen system, BUR system or CPE, CSM, CSPE, EPDM, NBP, PIB, PVC, TPO or TRE membrane system suitable for use with any roof insulation.

Note 1: Classification (A, B or C) and maximum incline will be the same as that of the Classified Roofing System (TGFU) currently limited to noncombustible deck.

[Last Updated](#) on 2006-01-10

[Questions?](#)

[Notice of Disclaimer](#)

[Page Top](#)

Copyright © 2008 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2008 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

